



Compact scale

915x

- ▶ High-resolution single-range scale
- ▶ Not approvable
- ▶ 5-key operation with freely assignable F key
- ▶ Weight units switchable between kg and lb
- ▶ Protection class IP 42



Features

- ▶ High-resolution single-range scale, not approvable
- ▶ Fast and stable standstill behaviour (filter type 3)
- ▶ 5-key operation with freely assignable F key
- ▶ Large LC display (no backlighting), character height: 25 mm
- ▶ Rechargeable battery operation and extra low-profile design facilitate flexible use in different locations
- ▶ Terminal can be pulled out by up to 30 mm. Benefits: Bigger weighing surface without obstructing the terminal, better access to plug-in connections
- ▶ Integrated USB interface type B (virtual serial interface)
- ▶ Fast connection of the power supply and USB interface, as it is on the side of the terminal
- ▶ Functions: Weigh, tare, plus/minus weighing, add, hold, user filter setting, print/EDV with variable print layout, auto tar
- ▶ Internal user calibration for location-specific adjustments
- ▶ Weight units switchable between kg and lb
- ▶ Weighing platform: Stainless steel 1.4301,
Base frame: Powder-coated steel
terminal housing: Plastic
- ▶ Mains operation: 100 – 240 V / 50 – 60 Hz
UK or US adapter, see accessories
Battery operation (6x AA batteries) or optional rechargeable battery operation with battery pack and charging circuit (battery life approx. 50 hrs., depending on settings)
- ▶ Energy-efficient due to integrated Auto-off function of the rechargeable battery with adjustable timer from 1 – 30 minutes or continuous operation
- ▶ Scale leveling up to 10 mm with 4 adjustable feet and spirit level
- ▶ Protection class IP 42
- ▶ Nominal operating temperature: -10 °C to 40 °C
- ▶ Scale dimensions / scale weight:
310 x 375 x 70 mm, 6 kg
400 x 400 x 75 mm, 11 kg
520 x 500 x 75 mm, 22 kg








Options

All interfaces have factory-preset print images and EDP data records for direct data output and data communication. These can also be individually adapted via the service programme 25641.10.001 (see accessories).


Products

Order number Variation	Approvable	Division g	Maximum load kg	Model substructure	Platform size mm
9150.01.040 Compact scale	No	0,1	3	Powder coated	310 x 275 x 70
9150.02.040 Compact scale	No	0,2	6	Powder coated	310 x 275 x 70
9150.03.040 Compact scale	No	0,5	15	Powder coated	310 x 275 x 70
9150.04.040 Compact scale	No	1	32	Powder coated	310 x 275 x 70
9151.02.040 Compact scale	No	0,2	6	Powder coated	400 x 300 x 75
9151.03.040 Compact scale	No	0,5	15	Powder coated	400 x 300 x 75
9151.04.040 Compact scale	No	1	32	Powder coated	400 x 300 x 75
9151.05.040 Compact scale	No	2	60	Powder coated	400 x 300 x 75
9152.04.040 Compact scale	No	1	32	Powder coated	520 x 400 x 75
9152.05.040 Compact scale	No	2	60	Powder coated	520 x 400 x 75

Accessories

Order number Variation		Description
2550.03.022		USB 2.0 cable 3 m with 2 plugs A-plug, B-plug, for IP 42 version (for integrated virtual serial USB interface and keyboard wedge)
2558.06.001		Extension module for serial interface (2 slots) and control light connection (optional interface modules required) Option must be included in the purchase order. Retrofits are not possible.
2563.49.003		RS422/485 interface installed (module 2563.50.00x / 2558.06.001 required) Any required options must be included in the purchase order. Retrofits are not possible
2563.21.007		RS 232 interface installed, 5-pin (module 2563.50.00x / 2558.06.001 required) Any required options must be included in the purchase order. Retrofits are not possible
2550.03.002		IT cable 2 m, 5-9 pin
2550.00.008		PC/computer data cable 2-10 m, 5-9 pin
5751.01.002		Dataset format, customer-specific
2795.20.001		Label printer, printing width up to 108 mm (thermo direct)
2550.03.010		Printer cable, 5-pin - 9-pin, 2 m (for printer 2795.20.001)
2795.12.002		Label printer with cut-off device, print width up to 104 mm (thermo-direct)
2795.14.005		Tape printer, paper width up to 76 mm (9 pin)
2550.03.007		Printer cable, 5-pin - 25-pin, 2 m (for printer 2795.12.002 / 2795.14.005)
2550.00.009		Printer cable, 5-pin - 25-pin, 2-10 m (for printer 2795.12.002 / 2795.14.005)
5751.01.001		Print format design, customer-specific
5751.01.004		Dataset/print format installation of existing or provided data
2562.01.004		Large display LED 95 mm, 5 pin plug with 10 m cable

Accessories

Order number Variation		Description
2562.12.001		Second display LED 38 mm, 5 pin plug with 15 m cable
2564.10.001		PC service software (print image design, data record, printer setup)
2564.20.002		Scale Connecting , software for transferring scale data to PC based software
2564.20.005		Scale Connecting Plus, extensive software for transferring scale data to PC-based software (with activation code)
2564.20.006		Software for linking scale to SAP R/3, single-user solution for SAP GUI via RS 232, USB or Ethernet
2564.20.010		Software for linking scale to SAP R/3, Server solution via Ethernet
2557.40.005		Battery incl. charging circuit installed for mains-free operation Option must be included in the purchase order. Retrofits are not possible
2557.25.004		US power adapter
2557.25.002		UK power adapter